

Standard Grounding Kit ,for cable 1/4"-7/8",1.0m

Product Image

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Suitable for screen diameter of cable OD 1/4"-7/8"
- Operation Temperature -40~70 °C
- Waterproof IP68



Description

Cyclone Grounding Kit for CAT5e, CAT6, CAT6A, and F/UTP 8mm Cables

Product Classification

Material Number	6003119
Status	Active
Detail Description	Standard Grounding Kit,for cable 1/4"-7/8",1.0m, installation accessories including

General Specifications

Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG 6
Grounding Strap Material	Copper, Tin-plated
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
Tape Material	PVC & Butyl

Dimensions	
Bonding Conductor Length	1.0m 39.3 in
Lug Hole Size	M8
Screw Size	M8x25
Electrical Specifications	
Contact Transition Resistance	Maximum 10mΩ
Packaging and Weights	
Height, Packed	180 mm 7.0 in
Width, Packed	310 mm 12.2 in
Length, packed	400 mm 15.75 in
Included	Grounding kit M8x25 screw M8 spring washer M8 flat washer M8 nut One roll of 6m PVC tape One roll of 0.6m butyl rubber Tape
UOM	1 Kit
Packaging	Bag
Weight, gross	0.367 kg 0.809 lb
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant